

Technical Data:

Material:

Solder Pin: Copper Alloy Tin plated

Insulator body(housing): Polyamide(Glass filled)(UL94V-0)

COLOR: GREEN

Electrical

Voltage rating: 300VAC

Current rating: 12 Amps/way max

Withstanding Voltage: 2500VAC(1min)

Test time=60sec/1pcs


Mechanical:

Operating temperature: -40°C to +105°C


Soldring reliability:

Test temperature= 250°C±10°C

5 seconds max



N=Number of contacts



P.C.B. LAYOUT

RoHS	TIN	99-02420-B054-A						
GP TYPE	PLATING	PART NUMBER						

6				_			1		7				,			1	DDO	11011	
	REV. DESCRIPTION E		ECN NO.	DWN.	CHK.	APVD.	DATE	SEE NOTE	APVD.			C-	-99-0242×	-2X \Bigg 🗲		1 0	F 4		
	Α	FIRST I	RELEASED	N1609507	Siyan			09-28'16	FINISH	1			DWG. NO			-	SHEET		ı
									SEE NOTE	CHK.				SEE TAE	3LE	1 : 1	[A3]	Α	ı
									MATERIAL		Siyan		PART NO).		SCALE	SIZE	REV.	ı
								ANGEL ±3°	ANIOSI I 71 DWAI				conn precision				ı		
									X.XX ±0.20 X.XXX ±0.15		09-28'16	6		tconi	n n	reci	SIOI	า	
									X.X ±0.30	ORIGIN	AL DATA								1
									X. ±0.50									mm	, ^
									TOLERANCES UNLESS OTHERWISE SPECIFIED	TITLE	Male te	rminal	block 8	BP 3.5mm	Pitch D	DIP TYPE	.	UNIT	A
1				1					T										ı
												G٢	IYPE	I PLATING		PARI	NOWRF	K	1

C-Drawing(Ass'y)
A3 Horizontal Type

RP0410A1

